

Applications:

Quick and easy LED replacement of T12 HO Fluorescent lamps

Features

System:

Input Voltage: 120-277 VDC
Rotatable R17D Sealed End Caps
Certification: UL
Rating: IP 65
Material: Aluminum
Operation Temperature: -22 °F - 140 °F
L70 Rating: 50,000 Hours
Efficacy: 125
CRI: >80
Warranty: 5 Years



**GENERAL PURPOSE
RETROFIT SIGN
CONVERSION
FOR USE ONLY IN
ACCORDANCE WITH
KIT INSTRUCTIONS**

KIT IS COMPLETE ONLY WHEN ALL PARTS
REQUIRED BY THE INSTRUCTIONS ARE PRESENT

Detail Specifications

Single Sided

Part Number	Replacement	Nominal Length	Watts	Lumens	Lumens/Ft	Input Amps @ 120V	Input Amps @ 277V
ZL-BETUBE-S18-65K	F18T12HO, Single Sided	18"	5	630	370	0.04	0.02
ZL-BETUBE-S24-65K	F24T12HO, Single Sided	24"	6	762	350	0.05	0.02
ZL-BETUBE-S30-65K	F30T12HO, Single Sided	30"	8	1000	371	0.07	0.03
ZL-BETUBE-S36-65K	F36T12HO, Single Sided	36"	10	1270	390	0.08	0.04
ZL-BETUBE-S42-65K	F42T12HO, Single Sided	42"	11	1375	374	0.09	0.04
ZL-BETUBE-S48-65K	F48T12HO, Single Sided	48"	13	1638	393	0.11	0.05
ZL-BETUBE-S60-65K	F60T12HO, Single Sided	60"	14	1750	350	0.12	0.05
ZL-BETUBE-S64-65K	F64T12HO, Single Sided	64"	15	1875	352	0.13	0.05
ZL-BETUBE-S72-65K	F72T12HO, Single Sided	72"	17	2125	354	0.14	0.06
ZL-BETUBE-S84-65K	F84T12HO, Single Sided	84"	20	2500	346	0.16	0.07
ZL-BETUBE-S96-65K	F96T12HO, Single Sided	96"	23	2875	351	0.19	0.08
ZL-BETUBE-S108-65K	F108T12HO, Single Sided	108"	25	3125	347	0.21	0.09
ZL-BETUBE-S117-65K	F117T12HO, Single Sided	117"	27	3402	349	0.23	0.10
ZL-BETUBE-S120-65K	F120T12HO, Single Sided	120"	28	3500	350	0.23	0.10

Double Sided

Part Number	Replacement	Nominal Length	Watts	Lumens	Lumens/FT Per Side	Input Amps @ 120V	Input Amps @ 277V
ZL-BETUBE-D18-65K	F18T12HO, Double Sided	18"	10	1310	370	0.08	0.04
ZL-BETUBE-D24-65K	F24T12HO, Double Sided	24"	12	1524	350	0.1	0.04
ZL-BETUBE-D30-65K	F30T12HO, Double Sided	30"	15	1905	371	0.13	0.05
ZL-BETUBE-D36-65K	F36T12HO, Double Sided	36"	17	2210	390	0.14	0.06
ZL-BETUBE-D42-65K	F42T12HO, Double Sided	42"	20	2500	374	0.17	0.07
ZL-BETUBE-D48-65K	F48T12HO, Double Sided	48"	22	2794	393	0.18	0.08
ZL-BETUBE-D60-65K	F60T12HO, Double Sided	60"	27	3375	350	0.23	0.10
ZL-BETUBE-D64-65K	F64T12HO, Double Sided	64"	28	3556	352	0.23	0.10
ZL-BETUBE-D72-65K	F72T12HO, Double Sided	72"	35	4375	354	0.29	0.13
ZL-BETUBE-D84-65K	F84T12HO, Double Sided	84"	40	5160	346	0.33	0.14
ZL-BETUBE-D96-65K	F96T12HO, Double Sided	96"	45	5625	351	0.38	0.16
ZL-BETUBE-D108-65K	F108T12HO, Double Sided	108"	47	5875	347	0.39	0.17
ZL-BETUBE-D117-65K	F117T12HO, Double Sided	117"	53	6678	349	0.44	0.20
ZL-BETUBE-D120-65K	F120T12HO, Double Sided	120"	55	6930	350	0.46	0.20