

UltraCanvas® Artist S250 is a 7.37 oz, 100% woven polyester that has been coated in polyurethane. The material is coated again (on one side only) with a digital coating. The unique coating process allows for a dual print surface using matte or gloss finishes. UltraCanvas Artist S250 may be used for indoor and outdoor applications. Available in widths of 126” and 196”.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN ISO 2286-2	100% PES	100% Polyester
Type of Coating	N/A	Polyurethane bath coated with digital top coat on one side	
Total Weight	DIN EN ISO 2286-2	250 g/m <sup>2</sup>	7.37 oz/yd <sup>2</sup>
Breaking Force [N/5cm]	DIN EN ISO 13934-1	Warp 2004 Weft 2220	Warp 314.7 Weft 359.7
Tear Resistance [N/25mm]	DIN EN ISO 9073-4	Warp – 307.6 Weft – 200.8	
Flame Resistance	DIN 4102	NFPA701, B1	

### Applications

	Art Reprographic	Banners Indoor	Banners Outdoor	Displays	Flags	Theatrical	Tradeshow	Wall Covering
Applications	■	■	■	■		■	■	■

### Ink Printability

Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■	■	■

### Available Sizes

Metric (m)	English (inches)
3.2, 5	126, 196

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of the material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)