



URKISYSTEM
INDUSTRIAL COATING SOLUTIONS



COMMITTED
TO EVOLUTION
PROUD PARTNERS OF CARWORX DISTRIBUTION

BESANATO 6713 | 6716 | 6714 | 6715
GLOSS | SEMI GLOSS | SAT | MATTE

NO SANDING
PRIMING
SEALER
REQUIRED!

Direct to Everything (DTE)

Polyurethane Binder

PRODUCT FEATURES

- 2 coat coverage
- High UV & chemical resistance
- Extreme weather resistant
- Simple & easy application
- Available in 4 different gloss binders



PAINT DIRECTLY ON ALL SUBSTRATES

• Aluminum • PVC • Acrylic • Polycarbonate • Galvanized • Brass • Bronze • Glass

SURFACE PREPARATION FOR BESA NATO

SURFACES	STEP 1 DEFECT REMOVAL	STEP 2 DEGREASE	STEP 3 FINAL CLEANING	STEP 4 FINAL WIPE
Aluminum / Metal Galvanized / Bronze / Brass	*If needed, use grit P220 and/or P320 followed by a maroon scuff pad	Degrease with BESA Urkisol 88	Clean surface with BESA SD - All Metal	Final wipe with low tack wipe cloth
PVC	If needed use a maroon scuff pad	Degrease with BESA Urkisol 88	Clean with BESA Urkisol 88 *PVC must be painted 5-10mins after cleaning	Final wipe with low tack wipe cloth
Acrylic / Polycarbonate	N/A	N/A	Clean surface with BESA Plastic Cleaner no. 94	Final wipe with low tack wipe cloth
Glass	N/A	N/A	Use BESA Glass Cleaner to remove any contaminants	Final wipe with low tack wipe cloth

*If there are no scratches, defects or imperfections, skip step 1 & 2 and go straight to step 3: Final Cleaning

Application Instructions

Mix and spray Besa Nato and/or Besa Nato Sat directly on the substrate following the proper mixing and application instructions from the technical data sheets.



3800 Transcanadienne, Pointe-Claire (QC), Canada, H9R 1B1

www.carworx.net | info@carworx.net | Tel: 514 745-5959 | Toll Free: 1-877-745-5959