Date: 2017.12.06 Revision date: 2017.12.06 Version: 1.0_En



Technical Data Sheet

Product: Dimense Ink

Producer: Veika UAB, Lithuania

Properties:

Appearance: Liquid Color: CMYK, Structural ink Odor: Slightly Viscosity: Less than 5 mPa·s, T@25°C (Brookfield) Surface tension: 25-35 dyne/cm Particle size: <150 nm (mean volume) Density: <1.1 g/cm³, T @ 25°C Solubility in water: miscible Media compatibility: Dimense media Print compatibility: DX 6; 7 print heads

Application:

Dimense inks should be used for digital printing only.

Product line:

- 440cc cartridge
- 1 liter bag for bulk ink system

Additional recommendations:

Recommended storage temperature: between +5°C and +35°C.

Shelf life in unopened container – 12 month.

For good processability use at room temperature: between +19°C and +25°C. Moisture <80%.

Should be used in its original package. Shake well before use. For industrial use only. Do not keep near fire or heat sources. Avoid direct sunlight. Do not store with chemicals or in high humidity conditions.

It is strictly forbidden to damage / cut / store products' original packaging once it's open. Do not pour the paint from the original packaging into any other container, because it influences the quality of the product (This note does not apply to paint bottles). In case of such violations VEIKA UAB takes no responsibility for the changes in product quality.