


DreamScape®



WALLWRAPS

REPOSITIONABLE PEEL & STICK WALLCOVERINGS



DreamScape®

WALLWRAPS

REPOSITIONABLE PEEL & STICK WALLCOVERINGS

NOW WITH SPECIAL EFFECT METALLIC OPTIONS!

EFFORTLESS, HIGH IMPACT THEMATIC GRAPHICS

REPOSITION/APPLY MULTIPLE TIMES

APPLY ACROSS WALLS, OVER MOLDINGS, AROUND CORNERS, ON CEILINGS

2-4 TIMES THICKER THAN OTHER WRAPS, MORE DURABLE, WILL NOT STRETCH OR TEAR EASILY

UNIQUE TEXTURES HIDE WALL IMPERFECTIONS, REDUCE GLARE & LIGHT HOT SPOTS

SEAMLESS COLOR PRINTING ON 54" WIDTHS IN 75', 150' AND 300' LENGTHS

NO OVERLAMINATION NECESSARY

PERFECT FOR WALL GRAPHICS, TRADE SHOW DISPLAYS, WIDE FORMAT MURALS, POP, CUSTOM PROMOTIONS, AND SEASONAL OR EVENT THEMING

COMMERCIAL STRENGTH MEDIA RECOMMENDED FOR: SHORT TO MEDIUM TERM WALL GRAPHICS, TRADE SHOW EXHIBITS, RETAIL AND POP DISPLAYS.

Product Packaging

Each roll is meticulously packaged in a re-usable tube. No splices, no creases, no flat spots for printer efficiency.

STD Lengths: 75' 150' 300'

STD Widths: 54" (+/- 1/8")

Physical Properties

Product Weight: 20.5 oz. per lineal yd with paper lining, 15 oz without lining

Film Weight: 14.5 oz. per lineal yd

Film Thickness: Ravello Texture - 0.013 in.
Caviar Texture - 0.013 in.
Classic Smooth - 0.011 in.
Brilliant Texture - 0.013 in.

Cold Crack Resistance @ 20F - no change

Heat Aging 7 days @ 158F - no change

Adhesive Properties

- Acrylic Based- Fire Retardant-Non Permanent.
- Low Tack and Peel - can be repositioned with no adhesive residue on removal
- Adheres to almost any smooth surface
- Tested on dry wall, glass, metal, wood paneling, and display board
- Shrinkage - Edge shrinkage of 1mm to 2mm is possible in the first 30 days
- A 0.5" seam overlap is recommended

For best results follow the DreamScape Wall Wrap Install Instructions.

Removability

When applied properly on a suitable surface, the adhesive will maintain it's standard release for 2 years. Beyond 2 years, the bond strength with the wall surface may gradually increase.

Durability and Longevity

This product is recommended for indoor use.

Outdoor life of unprinted material - 3 years

Indoor life of unprinted material - 10 years

Application

Wallwrap has been tested on drywall and many other smooth clean surfaces.

- Drywall requires a sealed surface with a level 4 or 5 finish.
- Uncured paints and primers can result in poor adhesion.

Due to the variability of surfaces, sealers, paints and environmental conditions, DreamScape does not accept claims for application or removal failures. It is the user's obligation to test and verify suitability prior to application.

AVAILABLE IN 4 TEXTURES:



WWW.DREAMSCAPEWALLS.COM

