

HP Latex 370 Printer

More unattended printing at lower cost of operation



Expand your applications—beat client expectations

- Get higher margins¹ printing on traditional signage substrates and beyond—even textiles²—up to 64 inches
- Reach new indoor spaces that solvent can't, like healthcare water-based HP Latex Ink prints are odorless
- Win new clients on eco standards—UL ECOLOGO®, UL GREENGUARD GOLD Certified inks; prints meet AgBB criteria³
- Impress clients—sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, 1200 dpi

Same-day delivery with more unattended production

- Confidently increase unattended printing—3-liter cartridges, HP Latex Mobile remote monitoring⁴
- Reach production speeds and avoid wait time—prints come out completely dry and ready to finish and deliver
- High quality at high speeds—334 ft²/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer⁵
- Deliver confidently—scratch-resistant prints last outdoors up to 5 years laminated, 3 years unlaminated⁶

For more information, please visit hp.com/go/Latex370

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at hp.com/communities/HPLatex

Keep running costs low with 3-liter ink cartridges

- Help reduce your cost per print with cost-effective, 3-liter HP 871 Latex Ink Cartridges1
- Save time—reduce cartridge changes and change ink cartridges while printing
- Reduce time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic⁷
- Less ink cartridge waste and disposal, and healthier HP Latex printing—no special ventilation or HAPs8
- For the HP Latex 370 Printer using cost-effective, high-capacity HP 871 3-liter Latex Ink Cartridges compared to the HP Latex 360 Printer using HP 831 775-ml Latex Ink Cartridges
- $Performance\ may\ vary\ depending\ on\ media—for\ more\ information, see\ hp.com/go/mediasolutions locator.$ For best results, use textiles that do not stretch. The ink collector is required for porous textiles.
- $Applicable to HP Latex Inks. \, ULECOLOGO @ Certification to UL2801 \, demonstrates that an ink meets a range of stringent criteria related to human health and environmental considerations (see \underline{ul.com/EL}).$ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org. HP WallArt printed on HP PVC-free Wall Paper and other prints on HP PVC-free Wall Paper printed with HP Latex Inks meet AgBB criteria for health-related $evaluation of VOC \,emissions \,of \,indoor \,building \,products, see \,\underline{umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building.}$
- Only HP Latex 300 series printers are supported. Additional printer support will be announced when available. HP Latex Mobile is compatible with Android™ 4.1.2 or later and iPhone mobile digital devices running iOS 6 or later, and requires the printer and the smart phone to be connected to the Internet. Support for tablet devices available as of September, 2015.
- Banner-quality prints in outdoor (4-pass 4-color) mode.
- Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation and the same of thein simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance.
- ICC profiling with the spectrophotometer does not support textiles and banners.
- Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected



Take advantage of third-generation HP Latex Printing Technologies

Water-based HP Latex Inks combine the best characteristics of solvent inks and water-based inks.

With HP Latex Inks, you can obtain outdoor durability and versatility across all common media types used in sign and display applications, together with high-quality, odorless prints, low maintenance, and health advantages9—even over eco-solvent inks.

HP Latex printing with the HP Latex 370 Printer can generate higher profit than eco-solvent—gain all the advantages of HP Latex printing, including wider application versatility with a single printer and prints that come out completely dry, allowing same-day delivery. Buy at an affordable price, and see how you can keep your running costs low.

The HP Latex 370 Printer features a number of significant innovations that take you beyond the limits of eco-solvent printing, creating new opportunities to expand your business.



HP Latex Inks and printheads

Take advantage of the versatile, durable performance of HP Latex Inks:


- 3-liter high-capacity ink cartridges for more unattended printing
- Scratch resistance comparable to hard-solvent inks on SAV and PVC banner you can consider unlaminated use for short-term signage¹⁰
- Six HP printheads provide 12,672 nozzles for robust and reliable quality print to print



HP Latex Optimizer

Achieve high image quality at high speed:

• Interacts with HP Latex Inks to rapidly immobilize pigments on the surface of the print



High-efficiency curing

High-speed printing with less energy and at lower temperatures:¹¹

- 17 m²/hr (183 ft²/hr) indoor quality, 31 m²/hr (334 ft²/hr) high-speed outdoor quality, 91 m²/hr (980 ft²/hr) maximum print speed¹²
- Prints are completely cured and dry inside the printer, and ready for immediate finishing and delivery



Color consistency

Print panels or tiles with excellent color consistency for an edge-to-edge match:

- i1 embedded spectrophotometer enables automatic calibration¹³
- Delivers consistent colors to
 2 dE2000¹⁴

⁹ Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.

¹⁰ Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media

Third-generation HP Latex Printing Technologies, including HP Latex Optimizer, reduce the temperatures and energy requirements of drying and curing HP Latex Inks Indoor prints (8-pass 6-color) mode; outdoor high-speed prints (4-pass 4-color) mode; maximum print speed (1-pass) mode.

Indoor prints (a-pass 6-color) mode; outdoor night-speed prints (a-pass 4-color,
 ICC profiling with the spectrophotometer does not support textiles and banners.

The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.





PRODUCT CERTIFIED FOR LOW CHEMICAL VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/GG UL 2818



PRODUCT CERTIFIED FOR REDUCED ENVIRONMENTAL IMPACT. VIEW SPECIFIC ATTRIBUTES EVALUATED: UL.COM/GG UL 2801


Build a healthier environment, inside and out¹⁵

Water-based HP Latex Inks enable a healthier approach to signage printing with advantages from the work zone to the point-of-display of finished prints:

- Healthier printing with HP Latex—no special ventilation, no hazard warning labels or HAPs¹⁵
- UL ECOLOGO® Certified HP Latex Inks meet a range of stringent human health criteria 16
- A safer workplace—HP Latex Inks are non-flammable, non-combustible and nickel free¹⁷
- UL GREENGUARD GOLD Certified HP Latex Inks; ¹⁸ produce odorless prints ideal for indoor display

Improve uptime and productivity with HP Services

HP Services offer you a broad portfolio of proven support programs to help keep your business running productively including HP Care Pack Services, preventive maintenance kits, and HP Support Programs.



HP Optical Media Advance Sensor (OMAS)

Precise and accurate motion control of media advance between print swaths:

• Controls registration automatically including double-sided prints with automated registration across sides19



Ink collector

Expand into textile signage:

• Print on a wide variety of textiles—including porous textiles—with the ink collector²⁰



HP Custom Substrate Profiling

Simplified and automated color management, directly from the front panel, 8-inch touchscreen:

- Pre-installed generic and HP substrate profile library
- Online substrate library access from the front panel
- Fine-tune existing profiles
- Create custom ICC profiles with the i1 embedded spectrophotometer²¹



HP Latex Mobile²²

Print with greater confidence while you're away from the

- Rely on alerts to inform you when attention is needed
- Know the status of your printer while you're away
- Remotely keep tabs on print jobs

Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the custom Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.

UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see ul.com/EL)

Water-based HP Latex Inks are not classified as flammable or combustible liquids under the USDOT or international transportation regulations. Testing per the Pensky-Martins Closed Cup method demonstrated flash point greater than 110°C. Nickel free demonstrated according to testing conducted for HP Latex Inks to achieve UL ECOLOGO® Certification. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see https://linearchy.org/lifecycle/based/criteria/related/to-human health and environmental considerations (see https://linearchy.org/lifecycle/based/criteria/related/to-human health and environmental considerations (see https://lifecycle/based/criteria/related/to-human health and environmental considerations (see https://lifecycle/based/criteria/related/to-human health and environmental considerations (see

UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

For best results use media options intended for double-sided printing.

Performance may vary depending on media—for more information, see hp.com/go/mediasolutionslocator. For best results, use textiles that do not stretch. The ink collector is required for porous textiles.

ICC profiling with the spectrophotometer does not support textiles and banners

Only HP Latex 300 series printers are supported. Additional printer support will be announced when available. HP Latex Mobile is compatible with Android M 4.1.2 or later and iPhone mobile digital devices running iOS 6 or later, and requires the printer and the smart phone to be connected to the Internet. Support for tablet devices available as of September, 2015

Technical specifications

Printing	D. C. C.		
	Printing modes	91 m²/hr (980 ft²/hr) - Max Speed (1 pass)	
		31 m²/hr (334 ft²/hr) - Outdoor High Speed (4 pass)	
		23 m²/hr (248 ft²/hr) - Outdoor Plus (6 pass)	
		17 m²/hr (183 ft²/hr) - Indoor Quality (8 pass)	
		14 m²/hr (151 ft²/hr) - Indoor High Quality (10 pass)	
		6 m²/hr (65 ft²/hr) - Backlits, Textiles, and Canvas (16 pass)	
		5 m²/hr (54 ft²/hr) - High Saturation Textiles (20 pass)	
	Print resolution	Up to 1200 x 1200 dpi	
	Margins	$5 \times 5 \times 0 \times 0$ mm (0.2 × 0.2 × 0 × 0 in) (without edge holders)	
	Ink types	HP Latex Inks	
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer	
	Cartridge size	3 liter, 775 ml	
	Printheads	6 (2 cyan/black, 2 yellow/magenta, 1 light magenta/light cyan, 1 HP Latex Optimizer)	
	Color consistency	<= 2 dE (95% colors) <= 1 dE average ²³	
Media	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paperbased media, backlit polyester film)	
	Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall-coverings, canvas, synthetics, mesh, textiles	
	Roll size	254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to 64-in) rolls with full support)	
	Roll weight	42 kg (92.6 lb)	
	Roll diameter	250 mm (9.8 in)	
	Thickness	Up to 0.5 mm (19.7 mil)	
Applications	Banners, Displays, Double-sided banners, Exhibition, Event graphics, Exterior signage, Indoor posters, Interior decoration, Light boxes – film, Light boxes – paper, Murals, POP/POS, Posters, Textile, Vehicle graphics		
Connectivity	Interfaces (standard)	Gigabit Ethernet (1000Base-T)	
Dimensions	Printer	2561 x 840 x 1380 mm (101 x 33 x 54 in)	
(w x d x h)	Shipping	2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in)	
	Shipping Printer	2795 x 760 x 1705 mm (110.1 x 30 x 67.2 in) 231.5 kg (510 lb)	
Neight Nhat's in the	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, load	231.5 kg (510 lb)	
Weight What's in the pox	Printer Shipping HP Latex 370 Princartridge, ink coll take-up reel, loar reference guide,	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick	
Weight What's in the pox	Printer Shipping HP Latex 370 Printer Cartridge, ink coll take-up reel, loan reference guide, Operating	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords	
Weight What's in the box	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, loareference guide, Operating temperature Operating	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F)	
Weight What's in the cox Environmental ranges	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing)	
Weight What's in the cox Environmental ranges	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage temperature	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) -25 to 55°C (-13 to 131°F)	
Weight What's in the cox Environmental ranges	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage temperature Sound pressure	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) -25 to 55°C (-13 to 131°F) 55 dB(A) (printing); < 15 dB(A) (sleep)	
Weight What's in the cox Environmental ranges	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage temperature Sound pressure Sound power	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) -25 to 55°C (-13 to 131°F) 55 dB(A) (printing); < 15 dB(A) (sleep) 7.4 B(A) (printing); < 3.5 B(A) (sleep) 4.6 kW (printing); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords;	
Weight What's in the book Environmental ranges Acoustic	Printer Shipping HP Latex 370 Printer cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage temperature Sound pressure Sound power Consumption	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) -25 to 55°C (-13 to 131°F) 55 dB(A) (printing); < 15 dB(A) (sleep) 7.4 B(A) (printing); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%)	
Weight What's in the box Environmental ranges Acoustic	Printer Shipping HP Latex 370 Printer Cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage temperature Sound pressure Sound power Consumption Requirements Safety	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) -25 to 55°C (-13 to 131°F) 55 dB(A) (printing); < 15 dB(A) (sleep) 7.4 B(A) (printing); < 3.5 B(A) (sleep) 4.6 kW (printing); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM) Compliant with Class A requirements, including: USA (FCC	
(w x d x h) Weight What's in the box Environmental ranges Acoustic Power	Printer Shipping HP Latex 370 Printer Cartridge, ink coll take-up reel, loar reference guide, Operating temperature Operating humidity Storage temperature Sound pressure Sound power Consumption Requirements Safety	231.5 kg (510 lb) 330 kg (728 lb) nter, HP 871 3-liter Latex Kit, printheads, maintenance lector, output platen protector, printer stand, spindle, ding accessory, user maintenance kit, edge holders, quick setup poster, documentation software, power cords 15 to 30°C (59 to 86°F) 20 to 80% RH (non-condensing) -25 to 55°C (-13 to 131°F) 55 dB(A) (printing); < 15 dB(A) (sleep) 7.4 B(A) (printing); < 3.5 B(A) (sleep) 4.6 kW (printing); < 2.5 watts (sleep) Input voltage (auto ranging) 200 to 240 VAC (-10% +10%) two wires and PE; 50/60 Hz (+/- 3 Hz); two power cords; 16 A max per power cord IEC 60950-1+A1 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New	

Ordering information

Product	L4R41A	HP Latex 370 Printer	
Accessories	F0M56A	HP Latex 64-in Printer 2-in Spindle	
	F0M58A	HP Latex 64-in Printer 3-in Spindle	
	F0M59A	HP Latex 3X0 User Maintenance Kit	
	F0M63A	HP Latex Media Loading Accessory	
	F0M64A	HP Latex 3X0 Edge Holders	
	D8J24A	HP Latex 360/370 Ink Collector	
Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead	
	CZ678A	HP 831 Yellow/Magenta Latex Printhead	
	CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead	
	CZ680A	HP 831 Latex Optimizer Printhead	
Original HP ink cartridges and maintenance supplies	G0Y79D	HP 871A 3-liter Cyan Latex Ink Cartridge	
	G0Y80D	HP 871A 3-liter Magenta Latex Ink Cartridge	
	G0Y81D	HP 871A 3-liter Yellow Latex Ink Cartridge	
	G0Y82D	HP 871A 3-liter Black Latex Ink Cartridge	
	G0Y83D	HP 871A 3-liter Light Cyan Latex Ink Cartridge	
	G0Y84D	HP 871A 3-liter Light Magenta Latex Ink Cartridge	
	G0Y85A	HP 871 3-liter Latex Optimizer Ink Cartridge	
	CZ682A	HP 831A 775-ml Black Latex Ink Cartridge	
	CZ683A	HP 831A 775-ml Cyan Latex Ink Cartridge	
	CZ684A	HP 831A 775-ml Magenta Latex Ink Cartridge	
	CZ685A	HP 831A 775-ml Yellow Latex Ink Cartridge	
	CZ686A	HP 831A 775-ml Light Cyan Latex Ink Cartridge	
	CZ687A	HP 831A 775-ml Light Magenta Latex Ink Cartridge	
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
Original HP large format printing materials	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.		
	HP PVC-fre	ee Wall Paper (FSC® and UL GREENGUARD GOLD Certified) ²⁴	
	HP Permanent Gloss Adhesive Vinyl REACH ²⁵		
	HP Backlit Polyester Film 🛟 26		
	HP Premium Satin Canvas		
	For the en	tire HP Large Format Printing Materials portfolio, please see a.com.	
Service and	U7VD2E	HP 2 year Next Business Day, DMR, and one SMK3 HW Support	
support	B4H70- 67105	HP Latex 300 series SMK3 Preventive Maintenance kit	

- The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) <= 2 dE2000. Reflective measurements on a 943 color target under CIE standard Illuminant DS0, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.</p>
- variations above 2 de.2000. Backilf substrates measured in transmission mode may yield different results.

 BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions. UL GREEMGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREEMGUARD Standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg or greenguard.org.

 This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.
- HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.













