

TECHNICAL INFORMATION**Product No. 801**

<u>Description</u>	General purpose masking tape
<u>Construction</u>	Crepe paper coated with rubber adhesive
<u>Application</u>	Masking of various surfaces, non-critical painting applications, packaging, bundling, holding
<u>Product Benefit</u>	Strong adhesion on a variety of surfaces. Rubber adhesive provides superior holding power in a variety of environments.
<u>Color</u>	Natural

Physical properties :

Total thickness (mils) PSTC-133	Tensile strength (lb/inch) PSTC-131	Elongation at break (%) PSTC-131	Adhesion to steel (oz/inch) PSTC-101
5.1 +/- 1%	18	8	Min 24

Test Condition

Temperature	: 23°C + - 1°C
Relative Humidity	: 60% + - 5%

Storage and Usage Condition

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight. Should be used within 6 months of date of shipment. Surface to which tape is applied should be clean, dry and free of dust, oil or grease and other contaminants.

Note :

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC or our procedures and the user must determine suitability for his purpose. There is no warranty of fitness for a particular application.