## **Neon - Glass Tubing**



## **VOLTARC Glass Tubing**

VOLTARC offers a broad selection of colors and the most shades of white available in glass tubing for Neon signs. Voltarc's Color Guard™ Coating process assures uniformity of coating thickness along the whole length of the tube and color consistency between batches. Diameters: 10, 12, 13 and 15mm. Cartons are 25 lbs. Clear Lead Glass is available in 50 lb. cartons.

#### WE WILL BREAK CARTONS UPON REQUEST.

	: 10, 12, 13 & 15 MM	
COLORS		
SNOW WHIT	E 6500	
WHITE 4500		
WHITE 3500		
BRITE WHIT	E 8300	
WARM WHIT	E 3000	
GREEN		
BLUE		
TURQUOISE		
AQUAMARIN	TE .	
PURPLE		
LAVENDER		
PINK WHITE		
MERCURY R	OSE	
ULTRABLUE		
SPARKLING	BLUE	
BLACKLIGH	Γ	
SDI		
HI-5100 WHI	Έ	

DOUBLE COATED LEAD GLASS 4' LENGTHS DIAMETER: 10, 12, 13 & 15 MM		
COLORS		
CLEAR GOLD II		
NEOBLUE		
NEORUBY		
DEEP GREEN		
CLEAR BRITE YELLOW		
MAJESTIC GOLD		
MAJESTIC ORANGE		

DIAMETEK:	5, 10, 12, 13, 15, 20 & 25 MM
COLOR	DESCRIPTION
CLEAR	REGULAR
CLEAR	HEAVYWALL
	(15 MM ONLY)
-	**50 lbs. CARTONS**

CLEAR LEAD GLASS

## **Neon - Glass Tubing**



## **EGL®** Glass Tubing

EGL® Glass Tubing for Neon signs offers the largest color selection and batch-to-batch color consistency. EGL Glass provides brilliant color which will not flake, even at the tightest bends. Diameters: 10, 12, 13 and 15mm. 4' lengths. Cartons are 25 lbs.

SIGNMATE IITM

#### WE WILL BREAK CARTONS UPON REQUEST.

SIGNMATE™ LEAD GLASS TUBING
4' LENGTHS
DIAMETER: 10, 12, 13 & 15 MM
COLORS
BRIGHTWHITE 8300 (V45B)
DAYLIGHT E65
SNOWHITE E30
SNOW WHITE 6500
BRITEWHITE E66
WHITE 4500 & V4500
WHITE 3500 & V3500
WARM WHITE E3000
PINK H 3700
GREEN E10
TROPIC GREEN
TURQUOISE E20 & E12
AQUA E21
AZURE
SEACREST
LAVENDER
LILAC
VIOLET
PURPLE
CORAL PINK
FLAMINGO
BLUE E40
HORIZON BLUE
MEDIUM BLUE

C.L. DESIGNER H TUBING 4' LENGTHS DIAMETER: 10, 12,	IGH OUTPUT GLASS  13 & 15 MM
COLORS	
C.L. DESIGNER 28	WARM (PINKISH)
C.L. DESIGNER 30	<b>^</b>
C.L. DESIGNER 35	
C.L. DESIGNER 41	
C.L. DESIGNER 65	COOL (BLUISH)

4' LENGTHS	
DIAMETER: 10, 12, 13 & 15 MM	
COLORS	
NEO BLUE	
VP GREEN	
CLEAR GOLD II	
CLEAR BRIGHT YELLOW	

ACCU WALL TUBING 4' LENGTHS COATED OR UNCOATED: 10, 12, 13 & 15 MM		
COLORS		
RUBY RED		
EMERALD GREEN		
ORANGE		
BROMO BLUE		
NOVIAL GOLD		
TANGERINE		

## **Neon - Electrodes**




#### **EGL®** Electrodes

EGL® manufactures over 75 standard and custom electrodes, the broad selection available. All EGL electrodes are made in the USA under rigid manufacturing procedures to ensure the highest quality standards.

NON-TUBULATED	DIAMETER	LENGTH	TUBULATED
12CF	10mm	2"	T12CF
9CF	12mm	2.5"	T9CF
9CMCF PREM. PLUS	12mm	2"	T9CMCF PREM. PLUS
9CCF PREM. PLUS	13mm	2.5"	T9CCF PREM. PLUS
13F SHORT	13mm	2"	T13F SHORT
8CF	15mm	2.625"	T8CF
8CCSF PREM. PLUS	15mm	2"	T8CCSF PREM. PLUS
8CMCF PREM. PLUS	15mm	2.375"	T8CMCF PREM. PLUS
8CCF PREM. PLUS	15mm	2.625"	T8CCF PREM. PLUS


\*ALL EGL ELECTRODES HAVE DURABLE FLEX LEADS\*





## **GRAB-IT™ Wireless Tube Supports**

Tubing snaps firmly into the clips, eliminating the need for wire twists. Clips are virtually invisible because they are transparent polycarbonate, allowing light to shine through. All GRAB-IT™ supports are spring loaded and provide a 1-3/4" stand off height to accommodate "double-back" tube thicknesses.



GRAB-IT Tube Supports		
FOR TUBE DIAMETER	BASE COLOR	
9mm	CLEAR OR BLACK	
10mm	CLEAR OR BLACK	
12mm	CLEAR OR BLACK	
13mm	CLEAR OR BLACK	
15mm	CLEAR OR BLACK	



## **EGL GASES - Standard & Blended**



GAS TYPE	CHARACTERISTICS
NEON	For clear red units or for coated tubing.
ARGON	For indoor use, mercury required. For low-voltage fluorescent tubes and lamps.
BLUE	Replaces #1050. Standard mix for warm climates.
K4	Cold weather gas. Best all-weather gas.Mercury required.
AV	VAILABLE IN .90 LITER FLASK, OR 25 & 50 LITER TANKS.
OTHER	TYPES OF GASES ARE AVAILABLE, PLEASE CALL.





## **Toggle Switches**

20 AMP, 125-277 VAC, 1.5 HP, 6" lead wires. Requires a 1/2" panel opening and has an on/off faceplate.



#### **G\*CUPS®**

Makes safe connections between two double-back electrodes, UL listed, won't burn or melt, won't track or arc-through, when protected from rain and snow. Can be mounted in any direction.



#### **Tube Supports**

UL listed, glass supports on either aluminum or brass bases.

ALUMINUM BASE	LENGTH	#/ <b>BOX</b>	
	1-3/4"	500	
	1-3/4" WITH TIE WIRES	500	
BRASS BASE	LENGTH	#/BOX	
	1-3/4"	500	
	1-3/4" WITH TIE WIRES	500	
	3-1/2"	100	
	5"	100	




#### **Glass Files**

Fine grain, double cross-cut.

**LENGTH** 

6"







## Glass Housings

UL listed, rated for 7500 VOLTS MAX.

PRODUCT #	DESCRIPTION
#100	LARGE
#200	SMALL
#200 P	SMALL PEANUT







## P-K Housing

ITEM	DESCRIPTION
PKHX	P-K HEX (FEMALE FITTING) COMPLETE
PKRG	P-K REG (MALE FITTING) COMPLETE
PKAC	P-K ACCESSORY BAG (1-2-3 CONNECTOR, STRAIN RELIEF)
PKC	ADJUSTABLE MOUNTING CLAMP





#### **Hi-VOLT Connector**

Ceramic, splices two GT0-15 wires, UL listed, rated for 7500V



#### **High Volt Splice Enclosure**

UL & CSA listed,. For dry, damp and wet locations. Borosilicate glass and metal. Non flammable.






#### **Mercury**

Triple Distilled

BOTTLE

1 LB.



#### **NonAsbestos**


High temp silicone coated fiberglass pattern material

**ROLL SIZE** 

WEIGHT

38" X 25 YARDS


14 LBS.



#### **CARBON PAPER**

Premium grade, extra heavy ink on kraft paper backing


COLORROLL SIZEWEIGHTBLUE36" X 25 YARDS15 LBS.



#### Pattern Paper

70 LB. kraft paper, 1" grid with 1/4" plot points

WIDTH	ROLL	WEIGHT
48"	110 YARDS	14 LBS.





#### Tie Wire

22 Gauge Copper Wire

**REEL SIZE** 

1 LB. 5 LBS.



#### **Electrode Button**

Brass with wings to wrap wires

**SPECIFICATIONS** #/BOX

.720 DIA. X .015 THICK



#### **Electrode Caps**

**Brass** 

SIZE	<b>DIMENSIONS</b>	#/BAG
15 mm LONG	.575 ID x .935 THICK	100
15 mm REG	.575 ID x .615 THICK	100
12 mm LONG	.450 ID x .615 THICK	100
12 mm REG	.450 ID x .935 THICK	100



#### **Ballast Wire**

UL Listed, 14 Gauge, 1000 Volt, 500' ROLL

**COLORS** 

**YELLOW** 

BLUE

RED

**ORANGE** 

**GREEN** 

**BROWN** 

**PURPLE** 


BLACK

WHITE

**BLUE/WHITE** 

ORANGE/BLACK

RED/WHITE



#### **Housing Caps**

UL Listed, fits any 10-32 housing

**SPECIFICATIONS** 

#/BOX

1.235 OD .900 HEIGHT

500



## **Cable Supports**

Porcelain, with metal screw

**SIZE** #/BOX

2-1/2" OVERALL LENGTH 100





#### **SNI-SNC**

Use with GTO 15 connections, 14-16 gauge wire connection

EYELET	(STUD)	#/BOX
SNI .265	(1/4")	250
SNC .200	(3/16")	200



#### Hi-Flex GTO-15 Plascene

UL Listed, flexible 105C rated

<b>GAUGE</b>	COLOR	ROLL
14	GREY	250'
14	BLACK	250'



#### Transformer Boxes

These top off model transformer boxes are made of electrogalvanized sheet metal and feature two louvers and four knockouts on each end.

#### **DIMENSIONS**

18" X 7" X 7"



#### Louvers

For heat ventilation



## **Adhesives**



## **Hypo Applicators**

Plastic bottles with hypo applicator tips for applying resin bond to letter trim and acrylic face.



#### **Resin Bond**

Resin Bond is a glue for use with acrylic plastics, specifically to glue cab plastic based sign trims to acrylics. Will not work with polycarbonate.

#### **SIZE**


QUART GALLON






## Neon - Sign Trim

## Sign-A-Trim Plastic Sign Trim





## **Snap Trim**


Made of UV resistant CAB and FOIL.


ITEM	LENGTH	#/BOX	COLORS
3/4"	8'	25	WHITE, RED, BLACK, GOLD, SILVER
1/2"	8'	30	WHITE, RED, BLACK, GOLD, SILVER

#### **Arrow Trim**

Made of UV resistant CAB and FOIL.

ITEM	LENGTH	COLORS
1"	10'	WHITE, RED, BLACK, GOLD, BRONZE, GREEN, TARGET RED,
		TEAL, YELLOW, METALLIC GREEN, CHROME, BROWN, IVORY,
		METALLIC RED, METALLIC BLUE, BLUE, BRONZE (313),
		ORANGE, BURGUNDY, BRUSHED GOLD, BRUSHED CHROME
2"	10'	WHITE, RED, BLACK, GOLD, BROWN, ORANGE, BRONZE,
		BRONZE (313), BLUE, CHROME, GREEN
1" REELS	150'	WHITE, RED, BLACK, GOLD, BRONZE, BRONZE (313), BLUE,
		GREEN, CHROME SILVER, SATIN SILVER
2" REELS	150'	WHITE, RED, BLACK, GOLD, BRONZE, CHROME SILVER,
		SATIN SILVER





150' SIGN TRIM DISPENSER REEL



#### **Short Stops**

Short Stops are used to insulate connections between electrodes and GTO cables. An internal ring makes short stops weather tight. UL listed.

CODE	SIZE	COLORS
SS0	10MM	GREY
SS3	13MM	BLACK, GREY, WHITE
SS5	15MM	BLACK, GREY, WHITE
SS6	16MM	GREY
WIDE		
SSW3	13MM	WHITE
SSW5	15MM	WHITE
SSW6	16MM	WHITE



#### **End Caps**

End Caps are used to insulate connections between electrodes and GTO cables, room for return provided. UL listed.

REY, WHITE
REY, WHITE
REY, WHITE
EY



#### **Long Sleeves**

Long Sleeves are used to insulate connections between electrodes placed 1" to 3" from each other. UL listed.

CODE	SIZE	COLORS	LENGTH
LS3	13MM	GREY	6"
LS5	15MM	GREY	6"



#### **GTO COVERING® 3870**

GTO Covering is used to protect and cover GTO cables in any indoor or outdoor sign enclosure, or in any outdoor channel letters, with any sign face material. Wall thickness is 1.8MM (.070") and acts as an effective corona barrier. Made of flame retardant Pyrolene<sup>TM</sup>II.

CODE	SIZE	<b>COLORS</b>
3870	O.D. – .515" I.D. – .375"	BLACK
		WHITE
		GREY



250 FEET PER ROLL

#### **GTO SLEEVING® 3730**

same uses as above but also for use with wide end caps and wide short stops.

COLORS
BLACK
WHITE
GREY







#### **PASS THRU™** Connectors

Pass Thru<sup>™</sup> Wiring Assembly Conduits are designed to protect GTO cables passing through walls, ceilings, raceways, channel letters and sign enclosures. Each Pass Thru<sup>™</sup> Connector comes with 4 locknuts, 2 plastic bushings, 1 sealing bushing and 1 ground ring.

PRODUCT CODE	SIZE
PTGR2	2"
PTGR4	4"
PTGR6	6"
PTGR8	8"
PTGR12	12"



#### **Straight Connector**

Female connector is used to twist-on fasten 3/8" flexible metallic conduit to a Pass Thru<sup>™</sup> conduit. Male connector is used to twist-on fasten 3/8" flexible metallic conduit to a transformer 1/2" knockout. Both are made of die-cast zinc.

STYLE	CODE	SIZE
FEMALE	SCF38	3/8"
MALE	SC38	3/8"
FEMALE	SCF12	1/2"
MALE	SC12	1/2"



Use the STRAIGHT CONNECTOR FEMALE to twist-on fasten 3/8 and 1/2 inch flexible metallic conduit to the PASSTHRU"



Use the STRAIGHT CONNECTOR to twist-on fasten 3/8 and 1/2 inch flexible metallic conduit to a transformer enclosure.



#### **High Voltage Connector**

High Voltage Connectors insulate between two GTO cables. Made from die cast zinc housing with mounting bracket, ground screw, one-screw duplex clamp and one piece insulator cap made of flame retardant Pyrolene<sup>TM</sup>.


PRODUCT	DESCRIPTION
HVC1001	ACCEPTS 1/2" CONDUIT



#### **Tube Supports**

Tube Supports are made of UV stabilized polycarbonate and are used to attach neon tubing to sign frames. One size fits all 12MM, 13MM and 15MM tubing.

PRODUCT	COLOR	SIZE
TS1000	CLEAR	ONE SIZE FITS
		12MM, 13MM OR 15MM





End Caps		
PRODUCT	SIZE	COLOR
C-10	10mm	GREY
C-12	12mm	GREY
C-12B	12mm	BLACK
C-13	13mm	GREY
C-13B	13mm	BLACK
C-15	15mm	GREY
C-12BC	15mm	GREY
C-D	DBL. CAP	GREY
181 11		


Short Stops	
PRODUCT	COLOR
102-SS	GREY
102-SS B	BLACK

For insulating G.T.O. lines		
PRODUCT	SIZE	ROLL
NMG-38	3/8"	100'
/		

# Sleeves PRODUCT SIZE S-10 10mm S-12 12mm S-13 13mm S-15 15mm

Quik-Support		
Tube Supports		
CODE	QUANTITY	
Q-S	100	
	500	
	1000	
	7	

Wiring Devices		
PRODUCT	DESCRIPTION	
101-E	1/2" SPACER	
101-F	G/F CONNECTOR	
101-G	CL G/F CONNECTOR	
101-N	1/4" NUTS	
	004	



## **Neon - Accessories**



#### **STA\*ZON Block Out Paint**

STA\*ZON Block Out Paint is used on neon sign tubing where portions of the tubing are not to show when the sign is illuminated. STA\*ZON Block Out is a rubber-based paint that will remain flexible and will not peel. It is quick-drying and weather-resistant.

STA*ZON	N Block Out Paint
COLOR	SIZE
BLACK	QUART
GREY	QUART
WHITE	QUART
STA*ZON BLOCK	QUART





## Aluminum Extension Posts




Allows for special applications where the tube needs to be extended several inches from the sign face. Cut off notches from 2-1/2" to 5-1/2". Comes complete with screws. (Tube support and base are not included.



## Slipstick Glass Bushing

Slipstick glass bushings are for use with high tension cables and have a one-way spring steel clip that slips easily into an automatic adjustment and won't back off. Has a secure rubber shoulder and heavywall insulating tubing.



## **Neon Tube Supports**

## **Clear-Vue Neon Tube Supports**

Optically clear acrylic support system for neon tube installations. For use wherever visual aesthetics are particularly important: architectural trim, window signage, art pieces, clocks, storefronts, etc. Tube attaches easily to support with a wire twist. For interior or exterior applications. Fits any size tubing.

ITEM	HEIGHT
NEC10	10mm (3/8 inch)
NEC20	20mm (3/4 inch)
NEC30	30mm (1-3/16 inch)
NEC40	40mm (1-9/16 inch)
NEC50	50mm (2 inch)
NEC60	60mm (2-3/8 inch)
NEC70	70mm (2-3/4 inch)

